## **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

Claim 1 (Currently Amended): A wireless communication terminal synchronization method in which data stored in a memory in each of plural wireless communication terminals is synchronized with each other, when a user selectively utilizes the plural wireless communication terminals by using a single subscriber information card, at least communicating operation in each of the wireless communication terminals being enabled by mounting thereon the subscriber information card that records subscriber information, the method comprising the steps of:

uploading from a first wireless communication terminal with the subscriber information card being mounted, to a server via a communication network, at least updated part of data which is stored in a memory in the <u>first</u> wireless communication terminal, in accordance with a user's request or automatically, said uploading being performed with only data updated after the subscriber information card was mounted on the first wireless communication terminal, while leaving the uploaded data in the memory in the first wireless communication terminal, wherein said uploading is allowed to be executed at least under conditions that the user is confirmed to be an authenticated user of said subscriber information card and an authenticated user of the first wireless communication terminal;

updating contents in a user's data storage area with the data being uploaded, in the server; downloading the data to a second wireless communication terminal via the communication network from the server, the data being confirmed in accordance with a user's request or automatically, as data to be downloaded to the second wireless communication terminal from the server, after the subscriber information card having been demounted is mounted on the second wireless communication terminal, said downloading being performed with only data which is present in the storage area of the server and which is not present in the memory of the second wireless communication terminal, wherein said downloading is allowed to be executed at least under conditions that the user is confirmed to be an authenticated user of said subscriber information card and an authenticated user of the second wireless communication terminal; and

updating the contents of the memory in the second wireless communication terminal, with the data having been downloaded from the server said uploading being performed with only data updated after the subscriber information card was mounted on the second wireless communication terminal, while leaving the uploaded data in the memory in the second wireless communication terminal, wherein said uploading is allowed to be executed at least under conditions that the user is confirmed to be an authenticated user of said subscriber information card and an authenticated user of the second wireless communication terminal.

## Claim 2 (Canceled)

Claim 3 (Currently Amended): The wireless communication terminal synchronization method according to claim 1-or 2, wherein, said uploading is allowed to be executed at least under conditions that the wireless communication terminal that requested the uploading is confirmed to be a terminal being associated with said subscriber information card in advance.

Claim 4 (Currently Amended): The wireless communication terminal synchronization method according to claim  $2 \underline{1}$  or 3, wherein, the conditions are confirmed on the terminal side.

Claim 5 (Currently Amended): The wireless communication terminal synchronization method according to any of claim 2, 3 or 4 1 or 3, wherein, the conditions are confirmed on the server side.

Claim 6 (Currently Amended): The wireless communication terminal synchronization method according to any of claims 1 to 5 claim 1 or 3, wherein, a data attribute as a target of said uploading and said downloading is registered in advance, and in each of the terminals, only the data having the data attribute registered in each own terminal becomes the target of the uploading and the downloading.

Claim 7 (Currently Amended): A wireless communication system comprising plural wireless communication terminals at least communication operation of which is enabled by mounting a subscriber information card recording subscriber information, and a server that is connected with the wireless communication terminals via a communication network, said server comprising:

Application No.: 10/591,406 4 Docket No.: 448252001800

a communication means interface which performs data communication with said wireless communication terminals via the communication network;

a storage unit which includes a storage area to store a copy of the data stored in said plural wireless communication [[i]] terminals; and

a server side synchronization <u>means</u> <u>engine</u> which synchronizes the data of a user stored in the wireless communication terminals and <u>the data</u> stored in the storage unit according to a request from <u>any one of</u> said wireless communication terminals;

each of the wireless communication terminals comprising:

a card mounting means <u>reader</u> which detachably mounts a subscriber information card;

a wireless communication means interface which is operable when said subscriber information card is mounted;

a memory means which stores user data; and

a terminal side synchronization means engine which requests execution of synchronization to said server after said subscriber information card is mounted, and uploading or downloading of data is being executed with said server as required, said uploading being performed with only data updated after the subscriber information card was mounted on the wireless communication terminal, leaving the uploaded data in the memory, and said downloading being performed with only data which is present in the storage unit of the server and which is not present in the memory of the wireless communication terminal; and

at least either one of said server and each of said wireless communication terminals further comprising:

an authentication <u>means engine</u> which allows only plural wireless communication terminals possessed by an identical user, to perform synchronization as to the user data of the user in the storage unit of said server;

said authentication engine being adapted to allow synchronization to be executed at least under conditions that the user who requested the synchronization is confirmed to be an authenticated user of said subscriber information card and an authenticated user of the terminal.

# Claim 8 (Canceled)

Claim 9 (Currently Amended): The wireless communication system according to claim § 7, wherein, said authentication means engine confirms that the user of the terminal that requested the synchronization is an authenticated user of said subscriber information card, on the basis of personal identification information being associated with said subscriber information card.

Claim 10 (Currently Amended): The wireless communication system according to claim § 7, wherein, said authentication means engine confirms that the user is an authenticated user of the terminal on the basis of personal identification information being associated with the wireless communication terminal.

Claim 11 (Currently Amended): The wireless communication system according to claim 7, wherein, said authentication means engine allows executing the synchronization under conditions that the terminal that requested the synchronization is confirmed to be the terminal that is associated with the subscriber information card in advance.

Claim 12 (Currently Amended): The wireless communication system according to claim 11, wherein, said authentication means engine is provided in the terminal so as to store in a memory of the terminal, the subscriber identification information recorded in said subscriber information card, and in performing authentication, it is checked whether the subscriber identification information of the subscriber information card mounted on the wireless communication terminal and the subscriber identification information stored in the memory of the terminal as a target for authentication match with each other, thereby confirming that the terminal requested the synchronization is a terminal being associated with said subscriber information card in advance.

Claim 13 (Currently Amended): The wireless communication system according to claim 11, wherein, said authentication means engine is provided in the terminal so as to store in the memory of the subscriber information card mounted on the terminal, the terminal identification information recorded in the terminal, and in performing authentication, it is checked whether any of the plural terminal identification information stored in the memory of the subscriber information card and the

terminal identification information recorded in the terminal as a target of the authentication match with each other, thereby confirming that the terminal requested the synchronization is a terminal being associated with the subscriber information card in advance.

Claim 14 (Currently Amended): The wireless communication system according to claim 11, wherein, said server comprises:

a subscriber managing database to register the subscriber identification information of the subscriber information card and terminal identification information of plural wireless communication terminals of the user in such a manner as being associated with each other; said authentication means engine is provided in said server to receive from the wireless communication terminal, subscriber identification information recorded in the subscriber information card and terminal identification information of the wireless communication terminal on which the subscriber information card is mounted, and confirms that the terminal identification information thus received is registered in the subscriber managing database, in such a manner as being associated with the subscriber identification information thus received, thereby confirming that the terminal that requested the synchronization is a terminal being associated with said subscriber information card in advance.

Claim 15 (Currently Amended): A wireless communication terminal at least communication operation of which is enabled by mounting a subscriber information card that records subscriber information, said terminal comprising:

- a card mounting means reader which detachably mounts a subscriber information card;
- a wireless communication means interface which is operable when the subscriber information card is mounted;
  - a memory means which stores user data; and
- a terminal side synchronization means engine which requests execution of synchronization to the server on the communication network after the subscriber information card is mounted, and executes uploading or downloading of data with the server as required, said uploading being performed with only data updated after the subscriber information card was mounted on the terminal, leaving the uploaded data in the memory, and said downloading being performed with

only data which is present in a storage unit of a server and which is not present in the memory of the terminal, and wherein said synchronization engine allows the synchronization to be executed at least under conditions that the user of the terminal who requested the synchronization is confirmed to be an authenticated user of said subscriber information card and an authenticated user of the terminal.

Claim 16 (Currently Amended): The wireless communication terminal according to claim 15, further comprising an wherein, said authentication means which engine allows only plural wireless communication terminals possessed by an identical user to perform synchronization for the user data of the user in a storage unit in said server.

#### Claim 17 (Canceled)

Claim 18 (Currently Amended): The wireless communication terminal according to claim 47 15, wherein, said authentication means engine confirms that the user of the terminal that requested the synchronization is an authenticated user of said subscriber information card, on the basis of personal identification information being associated with said subscriber information card.

Claim 19 (Currently Amended): The wireless communication terminal according to claim 47 15, wherein, said authentication means engine confirms that the user is an authenticated user of the terminal on the basis of personal identification information that is associated with the wireless communication terminal.

Claim 20 (Currently Amended): The wireless communication terminal according to claim 15, wherein, said authentication means engine allows executing the synchronization under conditions that the terminal that requested the synchronization is confirmed to be the terminal that is associated with said subscriber information card in advance.

Claim 21 (Currently Amended): The wireless communication terminal according to claim 20, wherein, said authentication stores in a memory means of the wireless communication terminal the memory of the terminal, the subscriber identification information recorded in said subscriber information card, and in performing authentication, it is checked whether the subscriber

identification information of the subscriber information card mounted on the wireless emmunication terminal and the subscriber identification information stored in the memory means of the terminal as a target for authentication match with each other, thereby confirming that the terminal requested the synchronization is a terminal being associated with said subscriber information card in advance.

Claim 22 (Currently Amended): The wireless communication terminal according to claim 20, wherein, said authentication means engine stores the terminal identification information recorded in the terminal in the memory in the subscriber information card mounted on the terminal, and in performing authentication, it is checked whether any of the plural terminal identification information stored in the memory in the subscriber information card and the terminal identification information recorded in the terminal as a target of the authentication match with each other, thereby confirming that the terminal requested the synchronization is a terminal being associated with the subscriber information card in advance.

Claim 23 (Currently Amended): The wireless communication terminal according to claim 15, further comprising:

a detecting means card detector which detects mounting and/or demounting of said subscriber information card, wherein, said terminal side synchronization means engine accesses said server triggered by detecting the mounting and/or demounting of said subscriber information card, and requests execution of the synchronization.

Claim 24 (Currently Amended): The wireless communication terminal according to claim 15, comprising a means battery remaining amount detecting section that detects a battery remaining amount, wherein, said terminal side synchronization means engine accesses said server triggered when the battery remaining amount becomes a predetermined level or less, and requests execution of synchronization including at least data uploading.

Claim 25 (Currently Amended): The wireless communication terminal according to claim 15, wherein, said terminal side synchronization means engine is provided with a judging means engine

which judges whether or not the terminal is in idle state, and executes the synchronization process when said judging means engine determines that the terminal is in idle state.

Claim 26 (Currently Amended): The wireless communication terminal according to claim 15, wherein, said terminal side synchronization means engine accesses said server in response to a directive from a user and uploads data as a target for uploading, and then, erases a predetermined data in the terminal all at once.

Claim 27 (Currently Amended): A server being connected via a communication network with plural wireless communication terminals at least communication operation of which is enabled by mounting thereon a subscriber information card that records subscriber information, said server comprising:

a communication means interface which performs data communication with said wireless communication terminals via the communication network;

a storage unit which has a storage area to store a copy of the data that is stored in said plural wireless communication terminals;

a server side synchronization means engine which performs synchronization with said wireless communication terminals for user data stored in said storage unit, in accordance with a request from said wireless communication terminals, said synchronization being performed with only data updated after the subscriber information card was mounted on one of the wireless communication terminals, while leaving uploaded data stored in the wireless communication terminal; and

an authentication means engine which allows only plural wireless communication terminals possessed by an identical user to perform synchronization for the user data of the user in the storage unit, wherein said authentication engine allow synchronization to be executed at least under conditions that the user is confirmed to be an authenticated user of said subscriber information card and an authenticated user of the wireless communication terminal on which said subscriber information card is mounted.

Claim 28 (Canceled)

Claim 29 (Currently Amended): The server according to claim 28 27, wherein, said authentication means engine confirms that the user of the terminal that requested the synchronization is an authenticated user of said subscriber information card, on the basis of personal identification information being associated with said subscriber information card.

Claim 30 (Currently Amended): The server according to claim 28 27, wherein, said authentication means engine confirms that the user is an authenticated user of the terminal on the basis of personal identification information that is associated with the wireless communication terminal.

Claim 31 (Currently Amended): The server according to claim 27, wherein, said authentication means engine allows executing the synchronization under conditions that the terminal requested the synchronization is confirmed to be the terminal that is associated with said subscriber information card in advance.

Claim 32 (Currently Amended): The server according to claim 31, further comprising:

a subscriber managing database to register the subscriber identification information of the subscriber information card and terminal identification information of plural wireless communication terminals of the user in such a manner as being associated with each other; said authentication means engine receiving from the wireless communication terminal, subscriber identification information recorded in said subscriber information card and terminal identification information of the wireless communication terminal on which the subscriber information card is mounted, and confirming that the terminal identification information thus received is registered in the subscriber managing database, in such a manner as being associated with the subscriber identification information thus received, thereby confirming that the terminal that requested the synchronization is a terminal that is associated with said subscriber information card in advance.